## **EMPACHER** SPECIFICATION SHEET nation: date: customer: phone address: fax signature of customer: requested date of delivery: e-mail type of boat: mould no .: rigging: normal: italien: italien: or: crew weight (average): <u>.....</u>kg pt stb stb stb pt stroke: stroke: stroke: rigger scull: $\Box$ R $\Box \chi$ $\square \chi$ $\Box$ C $\square$ R rigger sweep: bow bow bow coxswain: sitting in stern (four, eight) lying in bow (pair, four) 2 2 3 section: yes / no (seat no. 6 / 7) length of tracks: standard = 83cm(track without sketch for outrigger dimensions: other length:..... stoppers) pin sliding seat Spread: b) middle of boat-pin ☐ carbon with ☐ standard height ☐ medium (5mm lower) oval recesses Height: □ low (10mm lower) a) deepest point of seat (1) arbon with big ☐ high (5mm higher) to base of oarlock (2) (2) ☐ extra high (10mm higher) holes 0 ☐ height adjustable single scull stretcher side mounted at holes mounted on ratchet tracks on consoles П adjustment gates: Emp. insert gates: optionals: other:..... outrigger dimensions (s. sketch): round carbon profiles at canvas oarlock set in middle position carbon fin "model 2024" steering device integrated inside canvas scull Textrem decks sweep a) height starboard high performance edition .....cm (left hand): Textremdecks and carbon layer inside .....cm height portside Carbon ratchet tracks and stretcher pipe (right hand): (can only be ordered with round carbon profiles at canvas) .....cm full carbon stretcher with 4° vertical curve b) spread carbon shoeplate for variable shoe angle .....cm steering shoe right foot remarks / special requests: ☐ left foot seat no.: ..... seat no .: shoe sizes: 1 = 5 = 2 = (EU sizes) 6 =3 = 7 = 4 = electr. system: ☐ CoxBox cplt. ☐ CoxBox GPS cplt. ☐ CoxBox wiring only speaker numb.:... ☐ StrokeCoach Surge ☐ SpeedCoach GPS2 + Tr. P. ☐ only bracket for SpeedC. or StrokeC. ☐ T-bracket ☐ A-bracket boat cover: polyester, PVC coated, with zip cover for outrigger: qty.: .....